

### 3:1 Air Operated Oil Pump



Equipped with Lubricator

- Suitable for pumping through medium sized hose reel systems when one or two hose reels are required
- Air operated for integration into transfer system
- Long pumping life, easy to operate and maintain
- Smart design with fewer parts for less pump wear
- Differential air motor ensures smooth pumping
- Typical fluids handled include motor oil, synthetic oil, hydraulic oil, gear oil, automatic transmission fluid and coolant
- Suitable for oil up to SAE 150
- Supplied with adjustable 2" bung adaptor



Optional (Recommended)  
Pressure relief valve  
(DIT119572501) page 30



DIT11701031



DIT11701033



DIT11701034



DIT11701036

MODEL	DIT11701031	DIT11701033	DIT11701034	DIT11701036
Drum application	Stub	205 Litre drum	Stub	205 litre drum
Pressure ratio	3:1	3:1	3:1	3:1
Working pressure	70-115psi	70-115psi	70-115psi	70-115psi
Air consumption	@115psi 3.9 CFM	@115psi 3.9 CFM	@115psi 5.0 CFM	@115psi 5.0 CFM
Max flow rate (per min)	12 litres	12 litres	28 litres	28 litres
Suction tube diameter	42mm	42mm	42mm	42mm
Suction tube length	270mm	940mm	270mm	940mm
Air inlet connection	¼" BSP Female	¼" BSP Female	¼" BSP Female	¼" BSP Female
Oil outlet connection	½" BSP Male	½" BSP Male	¾" BSP Male	¾" BSP Male